



170-lb Dryer Spec-to-Spec Comparison



	AD-170	MILNOR - ML170	MILNOR - ML175	UNIMAC - UT170N	HUEBSCH - HT170	SPEED QUEEN - ST170	CONTINENTAL GIRBAU - CG165-75	PRIMUS - PT170	B&C - DE-170
Capacity	170 lb (77 kg)	170 lb (77 kg)	170 lb (77 kg)	170 lb (77 kg)	170 lb (77 kg)	170 lb (77 kg)	up to 175 (79 kg)	170 lb (77 kg)	170 lb (77 kg)
Height	100" (2,540 mm)	100" (2,540 mm)	100" (2,540 mm)	94" (2,387 mm)	94" (238 mm)	94" (2,387 mm)	94" (2,387 mm)	94" (2,387 mm)	94.25" (2,534 mm)
Width	55 7/8" n/a (1,419 mm)	55 7/8" n/a (1,419 mm)	55.75" (1,416 mm)	53 3/8" (1,349 mm)	53 3/8" (1,349 mm)	52.9" (1,349 mm)	53.12" (1,349 mm)	53.12" (1,349 mm)	56.25" (1,428 mm)
Depth	62 1/2" (1,587 mm)	68 1/2" (1,740 mm)	56" (1,422.4 mm)	67 7/8" (1,724 mm)	68 7/8" (1,749 mm)	69.8" (1,749 mm)	68.85" (1,748 mm)	68.85" (1,748 mm)	66.5" (1,689 mm)
Gas Inlet Size	1 1/2" (38.1 mm)	1 1/2" (38.1 mm)	1 1/2" (38.1 mm)	1" (25 mm)	1" (25 mm)	1" (25 mm)	1" (25 mm)	1" (25 mm)	1" (25 mm)
BTU Consumption	550,000 BTU/hr (137,500 kcal)	550,000 BTU/hr (137,500 kcal)	550,000 BTU/hr (137,500 kcal)	395,000 BTU (115.7 kW)	395,000 BTU (115.7 kW)	395,000 BTU (115.7 kW)	395,000 BTU (115.7 kW)	395,000 BTU (115.7 kW)	550,000 BTU/hr (137,500 kcal)
Cfm (60Hz)	3,700 Gas (104 cmm) 4,400 Steam (124 cmm)	3,700 Gas (104 cmm) 4,400 Steam (124 cmm)	3,700 Gas (104 cmm) 4,400 Steam (124 cmm)	2,450 (69 cmm)	2,450 (69 cmm)	2,150 (69 cmm)	2,150 (69 cmm)	2,450 (69 cmm)	4,000 (113 cmm)
Air Outlet Diameter	18" Gas (457 mm) 20" Steam (08 mm)	18" Gas (457 mm) 20" Steam (08 mm)	18" Gas (457 mm) 20" Steam (08 mm)	12" (304 mm)	12" (304 mm)	12" (304 mm)	12" (304 mm)	12" (304 mm)	16" (406 mm)
Airflow	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Cylinder Diameter	51 1/2" x 42 1/2" (1,308 mm x 1,079 mm)	51 1/2" x 42 1/2" (1,308 mm x 1,079 mm)	51 1/8" x 42 3/4" (1,298 mm x 1,085 mm)	50 3/4" x 42 1/2" (1,289 mm x 1,079 mm)	50.8" (1,290 mm)	50.8" (1,290 mm)	50.8" (1,290 mm)	50.75" (1,289 mm)	51.5" (1,308 mm)
Cylinder Volume	51.20 cu ft (1,449 L)	51.20 cu ft (1,449 L)	50.76 cu ft (1,437 L)	49.7 cu ft (1,407 L)	49.8 cu ft (1,410 L)	49.8 cu ft (1,410 L)	49.8 cu ft (1,410 L)	49.7 cu ft (1,407 L)	51.24 cu ft (1,451 L)
Drive / Fan Motor Hp	1 / 7-1/2 hp	1 / 7-1/2 hp	3 / 7-1/2 hp	3/4 / 3 hp	1.5 / 1.5 hp	1.5 / 1.5 hp	1.5 / 1.6 hp	3/4 / 3 hp	NL
Reversing	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Net Weight	2,103 Gas (953 kg) 2,259 Steam (1,024 kg)	2,103 Gas (953 kg) 2,259 Steam (1,024 kg)	1,848 Gas (838 kg) 2,001 Steam (907 kg)	1,575 Gas (716 kg) 1,675 Steam (761 kg)	1,575 Gas (714 kg) 1,675 Steam (759 kg)	1,400 Gas (635 kg) 1,550 Steam (705 kg)	1,400 Gas (635 kg) 1,550 Steam (703 kg)	1,575 (714 kg)	2,200 (997 kg)
Warranty	3 year	3 year	3 year	3 year	3 year	3 year	3 year	3 year	3 year
Factory Location	USA	USA	USA	USA	USA	USA	USA	Czech Republic	Thailand

All specs detailed above are for gas dryers.

